

MMK-AP_H1 STANDARD HIGH-WALL



Classic elegant unit with modern white colour panel and rounded surfaces to easily blend in with any room interior.

All year round comfort

- Total comfort is granted, thanks to the 70° directional auto-swing louver that provides uniform air distribution. Automatic louver swing patterns to evenly distribute the air into the room.

Healthy

- Enhanced indoor air quality filters.
- Self-cleaning function to effectively remove impurities in the air, ensuring the air flow remains clean and fresh.

Easy to use

- Wireless infrared remote control, allows simplified end user use and also gives direct access to the main operational controls and operating functions.

CAPACITY



2.2kW > 8kW

SOUND PRESSURE LEVEL



28dB(A)

OUTDOOR UNITS



Side Blow & MINI SMMS-e



SMMS-e



SHRM-e

LOCAL CONTROLS



IR control (included)



RBC-AMS55E-ES(EN)
RBC-AMS41E
RBC-AMT32E
RBC-AS41E

STANDARD HIGH-WALL Performances

Indoor unit	MMK-	AP0073H1/TR	AP0093H1/TR	AP0123H1/TR	AP0153H1/TR	AP0183H1/TR	AP0243H1/TR
Cooling capacity	kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	kW	2.5	3.2	4.0	5.0	6.3	8.0
Power consumption	kW	0.018	0.021	0.021	0.043	0.043	0.050
Running current	A	0.17	0.19	0.19	0.32	0.32	0.37
Starting current	A	0.22	0.24	0.24	0.41	0.41	0.47

STANDARD HIGH-WALL Physical data

Indoor unit	MMK-	AP0073H1/TR	AP0093H1/TR	AP0123H1/TR	AP0153H1/TR	AP0183H1/TR	AP0243H1/TR
Air flow (h/l)	m ³ /h	570/390	600/390	600/390	840/540	840/540	1020/570
Air flow (h/l)	l/s	158/108	166/108	166/108	233/150	233/150	283/158
Sound pressure level (h/l)	dB(A)	35/31/28	37/32/28	37/32/28	41/36/33	41/36/33	46/39/34
Dimensions (hwxwd)	mm	320x1050x228	320x1050x228	320x1050x228	320x1050x228	320x1050x228	320x1050x228
Weight	kg	15	15	15	15	15	15
Gas	in	3/8"	3/8"	3/8"	1/2"	1/2"	5/8"
Liquid	in	1/4"	1/4"	1/4"	1/4"	1/4"	3/8"
Drain port diameter	mm	16	16	16	16	16	16
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50